

Depth of Cover Specialists

The Best Tool for the Job:

A review of current methods and technologies for locating underwater utilities at dredging sites

Pete Weber Chief Operations Officer (619) 566-6783

New Orleans / San Diego

Sales@DoCMapping.com www.DepthofCover.com





The Right Tool for the Job





DoC Mapping is not beholden to any one tool or approach. Different tools work in different situations.

The following tools are in our arsenal.

- Probing
- Sub-bottom Profiling
- Advanced Sonar Technologies
- Electromagnetic Locating
- Electromagnetic Modeling

The best survey results include more than one type of data that cross verify each other.



The goal is the deliver results at are:

- Transparent!
- Verifiable!
- Repeatable!



Probing, the old school method...



Probing has been used traditionally for shallow water surveys for a number of reasons:

- Simple
- Inexpensive equipment
- Accurate depth and position if done right



It has a few downsides though:

- Slow!
- Wide point spacing
- You need to have a pretty good idea of where the pipe is
- Need good weather



Acoustics / Sub-Bottom Profiling



mantes	27160.0	27180.0	27200.0	21220.0
1685	1.			NAME AND DESCRIPTION OF
1.575	10000		NER ER STATE	
19.8		A COMPANY AND A COMPANY		THE REPORT
100		特別の一部ではは		Contraction of the local division of the loc
and the	Contraction of the	-	-	Real day 1.1
1999	10	CALL IN COMPANY	A	Charles and the second second
ALL NO.	1966-1679	THE CLORES		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
PHE 4	TOP OF PIP	F LA BASSING R	TAX RANGE AND A	COLUMN DESIGN
1.84				
1000	11111		And the second	NUMBER AND POST
	10000	A DECEMBER OF STREET		A
1200		10.000	1.1	Sector Labor A
1000	Color and	A REAL PROPERTY.	STA BOARD	A DECKS AND A DECKS
20 B		67 6 C	AND 14 19 19	Contraction in the second
2018	10.2 10.0 10		2010年1月1日日	ADDRESS COMMENTS
1.1	100 200 4	Res and the second		
	** <u>1997</u> 1963)	And an other states of the	SEN. MAR	STREET, STREET
1.16.2	1 284,7854	C HEAD I BANK TO A		AND MODEL & AD
11	ALC: NO LOC	THE R. LEWIS CO.	100 B 100 B 100	THE PARTY AND
行政 3	1510130		CELER MACHE	
100000	1 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	STARLES AND STREET	The second second second	大王のかってあったものでも



Sub-bottom profiling has been around for years and is sometimes used for DoC Surveys.

Pros:

- Large survey areas possible
- Very accurate Z measurement
- No signal required
- Works on a variety of materials

- Interpretation can be a "dark art"
- Post-processing can take a long time
- Highly dependent on seabed material
- X/Y coordinates can be less accurate
- Expensive / complicated





Advanced Sonar Technologies





Cracked



MultiBeam and MultiPhase sonar technologies provide much higher resolution of bottom features:

Pros:

- Amazing detail on bottom features •
- Provides clues to the pipes true location .
- **Great for characterizing exposures**
- Great for quantifying scour .

- Only shows features on the riverbed •
- Post-processing can take a long time
- Can be expensive and complicated to do right .



Electromagnetic Remote Sensing



Electromagnetic remote sensing uses magnetometers and gradiometers to measure the magnetic field associated with the pipeline.



Three basic types:

- Passive magnetometers
- Electromagnetic Locators
- Electromagnetic Modelers









Electromagnetic Locating

Locators utilize a set of sensors that detect the orientation and relative strength of the magnetic field emitted from the pipe.

Pros:

- Fairly simple / inexpensive
- Fast
- Can be very accurate
- Large areas can be covered

- Signal required
- Relies on operator to interpret the magnetic field
- Operator must precisely position the antenna and hold it still
- Data in invisible once reading is taken
- Difficult in deep water, swift currents







Electromagnetic Modeling

Modelers use and array of gradiometers to measure the orientation and relative strength of the magnetic field in order to generate model of the field.

Pros:

- Large survey areas possible
- All data is saved for later review
- Accurate X, Y and Z positions, GPS Integration
- Works while moving, multiple readings per second.
- Excellent for deep water, currents, long pipe runs

- Signal required
- Complicated / Expensive



Signal!





- No signal required
- Uses intrinsic magnetic field
- Need to be close
- Very susceptible to noise

Active magnetic field detection:

- Signal application required
- Easy to isolate signal
- Strong signal
- Field strength / frequency is tunable







I love it when a survey plan comes together!



www.DepthofCover.com



I love it when a survey plan comes together!



Locate data points portrayed in congruence with side scan sonar imagery confirms a spanning section of pipeline with attached river weights still resting on the lake bed.



PROFILE VIEW

www.DepthofCover.com

MAPPING

01+00

01+50

02+00

Bank Topo

02+50

I love it when a survey plan comes together!

06+50

07+00



www.DepthofCover.com

04+00

— MB Bathy (11/22/15) — MB Bathy (4/22/16) — T.O.P. (DoC Mapping) — +VSDV (DoC Mapping)

04+50

05+00

05+50

----- ILI Data

06+00

03+50

03+00





www.DepthofCover.com



Pete Weber

Chief Operations Officer (619) 566-6783

Pete.@DoCMapping.com www.DepthofCover.com

