




Presented by

Katy Gross, PE Anchor QEA










UPLAND
CLEANUP
SITES

EARLY ACTION AREAS



TIMELINE



CONTAMINANTS


PCBs

Arsenic

Dioxins/ Furans

PAHs


Others




3 Phases of Pre-Design Investigations


Phase I


- Define horizontal extents
- Phase II
 - Refine horizontal extents
 - Vertical data collection
 - Collection of other engineering data (e.g., geotechnical data)
 - Used for 30% and 60% RD
- Phase III
 - Address data gaps identified during 30% and 60% RD
 - Final remedial action level
 (RAL) exceedance areas for
 90% and 100% RD







- Phase
 - Define horizontal extents
- Phase II
 - Refine horizontal extents
 - Vertical data collection
 - Collection of other engineering data (e.g., geotechnical data)
 - Used for 30% and 60% RD
- o Phase III
 - Address data gaps identified during 30% and 60% RD
 - Final remedial action level (RAL) exceedance areas for 90% and 100% RD






- Phase
 - $\circ\;$ Define horizontal extents
- o Phase II
 - Refine horizontal extents
 - Vertical data collection
 - Collection of other engineering
 - data (e.g., geotechnical data)
 - \circ Used for 30% and 60% RD
- Phase III
 - Address data gaps identified during 30% and 60% RD
 - Final remedial action level (RAL) exceedance areas for 90% and 100% RD





Data Interpolation


- Indicator kriging for PCBs
 - Geostatistical interpolation method
 - Maps probability of remedial action level (RAL) exceedances
- Thiessen polygons for all other contaminants
- Merged to create RAL exceedance areas



Engineering Considerations


Engineering Considerations for Remedial Action Area Boundaries

- Geometry
- Site conditions
- Operational and administrative
- Review of data interpolation uncertainty
- Constructability and minimizing risk of recontamination




Engineering Considerations:Site Conditions


- Geotechnical stability
- Offsets from structures and utilities
- Historical dredging



Engineering Considerations: Operational/Administrative


Early action areas, Ecology-led upland cleanups, habitat areas, ROD requirements






Engineering Considerations:

Review of Data Interpolation Uncertainty



Engineering Area A: Required Dredge Elevation -21.5' MLLW **Considerations:** Constructability **Area C:** Required Dredge and Minimizing Elevation -21.0' MLLW Risk of Recontamination Area B: Required Dredge Elevation -22.0' MLLW **Area D:** Required Dredge Elevation -23.0' MLLW

- Completing 100% design now
- Bid advertisement in January 2024
- Construction to begin
 October 2024
- Three in-water work seasons









What questions do you have?

